

ECCO 68AS PRO LEATHER



Special versions of Ecco 68AS and ASH adapted for the leather industry, well suited for easy installation and maintenance on reciprocators or carousels. Ecco 68 Pro-Leather spray guns benefit from all key characteristics that made the previous generations 60AS and 65AS Pro-Leather so successful, incorporating the new 68 revolutionary design. The simple baseplate mounting solution for easy maintenance is now combined with Tungsten Carbide needle for highest durability. Also the new accurate fluid flow control with reproducible setup on the line, fixed air cap position and more.

TECHNICAL DATA

Fluid nozzle	diam 0,3-2,7 mm
Air connection	Ø 10/8 and 8/6
Air consumption	max 900 lit/min
Fluid connection	Ø 8/6
Size (WxHxL)	75 x 75 x 130mm
Weight	gun 460g / gun+plate 790g

FLUID NOZZLE DIAM. MM	AIR CAP	NEEDLE TYPE	ORDERING NUMBER	VISCOSITY DIN (SEC)
1.1	T272	HA00468	8611 6169 02	5-25
1.3	T260	A0468	8611 6169 01	10-30
1.3	T272	HA0468	8611 6169 03	10-30
G1.2	6514	HA0468	8611 6169 30	5-25
G1.3	6514	HA0468	8611 6169 31	10-30
G1.4	6514	HA0468	8611 6169 32	15-40

NEZÁVAZNÁ POPTÁVKA