

ECCO FLOW AL15



Ecco Flow AL 15 and SS15 are metallic diaphragm pumps with very high performance, flow capacity, proven reliability and durability. The pump housing is made in aluminium or stainless steel. All components in direct contact with the fluid, such as valves, diaphragms, covers and manifolds are manufactured in materials which are highly resistant to physical and chemical wear, thus allow you to handle most existing fluids.

Transfer pump Ecco Flow AL15	8621 0520 01
Transfer pump Ecco Flow SS 15	8621 0510 01
Complete pump panel	8613 2311 65
Service set for paint part AL15	6804 0141 30
Service set for fluid part SS15	6804 0141 20
Set with o-rings for AL15/SS15	6804 0141 40
Return valve set for AL15/SS15	6804 0141 10

TECHNICAL DATA

Pressure Ratio	1:1
Capacity lit/min	0-52
Inlet air pressure min/max (bar)	1-8
Air consumption at 8 bar (lit/min)	0-375 approx.
Self-priming	Yes
Dry lift capacity at 6,8 bar	4,9
Size of max pumpable particles (mm)	2,0 mm
Air inlet	G 1/4 external
Fluid inlet	G 1/2 internal
Fluid outlet	G 1/2 internal
Adjustable fluid connections	Yes
Weight (kg)	3,8
Housing material	Aluminium
Diaphragm material wet/dry side	PTFE
Sealing rings	PTFE
Valve seat / ball	Stainless steel / stainless steel

NEZÁVAZNÁ POPTÁVKA