

ECCOMANT AIR ASSIST TIP



Tungsten carbide nozzle designed for the automatic air assisted spray gun Ecco 380AA. Manufactured to high standards of accuracy for long lifetime and precise spray pattern.

The spray tip is held in correct position by the retaining ring. Use the table below for selection of the correct spray tip.

Recommended strainer in delivery circuit:

Orifice \varnothing 0,011-0,013 mm: 200 mesh

Orifice \varnothing 0,015-0,019 mm: 100 mesh

NEZÁVAZNÁ POPTÁVKA

ORIFICE \varnothing INCH/MM	FAN ANGLE°	CAPACITY (LIT/MIN)*
0,011 / 0,28	20°	0,54
0,011 / 0,28	30°	0,54
0,011 / 0,28	40°	0,54
0,011 / 0,28	50°	0,54
0,011 / 0,28	60°	0,54
0,013 / 0,33	20°	0,82
0,013 / 0,33	30°	0,82
0,013 / 0,33	40°	0,82
0,013 / 0,33	50°	0,82
0,013 / 0,33	60°	0,82
0,013 / 0,33	80°	0,82
0,015 / 0,30	20°	1,15
0,015 / 0,30	30°	1,15
0,015 / 0,30	40°	1,15
0,015 / 0,30	50°	1,15
0,015 / 0,30	60°	1,15
0,015 / 0,38	80°	1,15
0,017 / 0,43	40°	1,50
0,017 / 0,43	50°	1,50
0,017 / 0,43	60°	1,50
0,017 / 0,43	80°	1,50
0,019 / 0,48	40°	1,91
0,019 / 0,48	50°	1,91
0,019 / 0,48	60°	1,91
0,019 / 0,48	80°	1,91