

ECCO 35



The manual spray gun Ecco 35, available both as conventional and as HVLP, is made in anodized aluminium in order to optimize balance and weight. The gun can be used for spraying water born paint and high solid paint. The inside paint channels are designed for easy cleaning, saving time and solvent when changing colour. Both the amount of air and paint, as well as the spray pattern can be adjusted on the gun. The Ecco 35 is available in conventional or HVLP version and can be equipped with a wide range of fluid nozzles, air caps and needles to ensure an optimized application for all standard paint types.

TECHNICAL DATA (KONVENTIONAL)

Paint nozzles	0,2-2,7mm
Paint connection	G 3/8
Air connection	G 1/4
Air pressure max (bar)	7
Air consumption	250-700 lit/min
Weight	521g

NEZÁVAZNÁ POPTÁVKA

PAINT NOZZLE Ø MM	AIR CAP TYPE	NEEDLE MATERIAL	ORDERING NO.	VISCOSITY DIN4 (SEK)
1,1	T278	SS	8611 3548 51	12-22
1,1	T272	Nylon	8611 3572 11	12-22
1,3	T272	Nylon	8611 3572 13	25-40
1,3	T272	SS	8611 3548 53	24-40
1,3	T272	SS	8611 3548 54	24-40
1,5	T274	SS	8611 3548 55	25-45
1,5	T274	Nylon	8611 3572 15	25-45
1,8	T272	Nylon	8611 3572 18	35-60
1,8	T272	SS	8611 3548 58	35-60
2,1	T374	Nylon	8611 3572 21	40-70
2,1	T374	SS	8611 3548 59	40-70
2,7	T474	Nylon	8611 3572 27	40-90
2,7	T474	SS	8611 3548 77	40-90
HVLP guns:				
G 0,9	6509	Nylon	8611 3540 09	10-22
G 0,9	6509	SS	8611 3548 09	10-22
G 1,1	6511	Nylon	8611 3540 11	20-40
G 1,1	6511	SS	8611 3548 11	20-40
G 1,4	6514	Nylon	8611 3540 14	25-45
G 1,4	6514	SS	8611 3548 14	25-45
G 1,8	6518	Nylon	8611 3540 18	35-60
G 1,8	6518	SS	8611 3548 18	35-60
G 2,1	6521	Nylon	8611 3540 21	50-75
G 2,1	6521	SS	8611 3548 21	50-75
G 2,7	6527	Nylon	8611 3540 27	40-90
G 2,7	6527	SS	8611 3548 27	40-90