

ECCO POWER FLOW 860S



Ecco Power Flow 860S is suitable for medium and high viscosity materials. The pump is designed for high performance purposes and feeds large nozzles or several spray guns at the same time. Suitable for protective coatings, wood and car manufacturers. A single spraying operation produces high coating thickness and high performance characteristics. The use of solvents is cut to a minimum, because highly viscosity materials can be applied directly. There is hardly any overspray or spray mist with the environment remaining clean. The Ecco equipment stands for superb performance quality and meet all technical requirements. The advanced design and conception correspond to all applicable safety specifications and regulations. Sophisticated engineering, functional dependability and easy handling are only a few of the outstanding features of this equipment. The pump can be delivered bare, on a trolley for easy mobility painting big parts or on a wall bracket.

TECHNICAL DATA

Pressure Ratio	60:1
Capacity (cc/double stroke)	110
Paint connection, suction/pressure	G1 male/ 1/4-18 NPSM
Max air inlet pressure, bar (psi)	6 (87)
Max air consumption (lit/min)	2300
Max output pressure (Bar/Psi)	360 (5221)
Weight (kg)	73

PUMP TYPE	TYPE OF ASSEMBLY	ORDERING NUMBER	WEIGHT
860S-A	Bare pump	8621 0724 00	25 kg
860S-B-A	Bracket for wall	8621 0724 01	26 kg
860S-T-A	Trolley	8621 0724 03	28 kg

NEZÁVAZNÁ POPTÁVKA